

*Professional Quality*



**2028**

**CONTACT SPRAY  
SUPER ADHESIVE**

**V&S #2028 CONTACT SPRAY SUPER ADHESIVE**  
*V&S 2028 is a high solids aerosol contact adhesive that meets CARB requirements. It is suitable for permanently bonding a wide range of materials including decorative laminates, edgebanding, veneers, glass, fiberglass, headliners, fabric, particle board and many plastics. Water resistant and temperature resistant to over 200°F*

**OUTSTANDING FEATURES**

- **SPRAY GRADE**
- **STRONG BONDS**
- **HIGH TEMPERATURE RESISTANCE**
- **SCAQMD COMPLIANT**
- **OTC COMPLIANT**
- **LEED COMPLIANT**

***CARB Compliant  
High Temperature Resistance  
Fast Drying***

**V&S #2028 CONTACT SPRAY SUPER ADHESIVE**

is suitable for permanently bonding a wide range of materials including decorative laminates, edgebanding, veneers, glass, fiberglass, headliners, fabric, particle board and many plastics. Water resistant and temperature resistant to over 200°F

**STORAGE:** Store in clean, dry area away from sparks and heat sources. Recommended to store container off the floor if temperatures below 60°F.

**MARKETS:** This product is ideal for use in the automotive, marine, aviation, and industrial markets where higher heat resistance is required. Applications include automotive trim, headliners, engine compartment insulation pads, conversion van and RV trim and insulation panels, marine/aviation carpet and panel applications, and more.

**INSTRUCTIONS:** V&S 2028 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive approximately 3-5 mils thick on both surfaces. Allow to tack. Place the surfaces together and apply pressure evenly across the full bonding surface.

**FOR BEST RESULTS:** Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If assembly is delayed and the adhesive becomes too dry, apply a light coating again.

**PRODUCT SPECIFICATIONS:**

Appearance:	Liquid, Clear Shear
Adhesion:	>100PSI and >200°F
Base:	Synthetic Polymers
Solvent:	Blend of hydrocarbons and isobutene/propane propellant
Shelf Life:	12 Months (unopened)
Freezing:	Not damaged by freezing but return to room temp before use
Packaging:	12, 24 fl.oz. Containers/Case

Adhesive Solutions, Inc.  
10106 Romandel Ave.  
Santa Fe Springs, CA 90670  
800.669.8871  
eFax: 562.444.6088  
www.adhesivesolutions.com



**Disclaimer of Warranty:** Adhesive Solutions expressly disclaims all warranties either expressed or implied, including but not limited to merchantability, fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost. This provision relates to all sales and cannot be modified.

**Manufacturer:** Manufactured for Adhesive Solutions, 800-669-8871  
See SDS Data Sheet for Proper Handling and Safety Information